



## Strong Adhesive Labels Tyre Label

DURABLETAG

# PPL5150

TC TOP WHITE PP44 SRH -WG2S FSC

**Product Code :** PPL5150

**Product Name :** TC MAT WHITE PP44 SRH -WG2S FSC

**Facestock :** Bioriented top - coated white polypropylene, extreme resistance to tear, puncture and tear propagation. Specially for labelling rough surfaces.

**Basis Weight :** 44 g/m<sup>2</sup> ISO 536

**Caliper :** 58 µm ISO 534

**Adhesive :** Aggressive adhesive , Synthetic Rubber Hotmet

**Liner :** Supercalendered glassine paper, white colour, two sides siliconize

**Basis Weight :** 78 g/m<sup>2</sup> ISO 536

**Caliper :** 68 µm ISO 534

**Total Caliper :** 187 µm±10% ISO 534

**Initial Tack :** 45 N ±10 / 25mm FTM 9 Glass

**Peel Adhesion 90° :** 25 N ±3 / 25mm FTM 2 St

**Service Temperature :** - 20 °C to 70 °C (158 °F)

**Min. Application :** Temp. 0 °C

**Adhesive Performance :** SRH uses an aggressive formulation developed for labelling rubber with irregular and curved surfaces. It withstands typical chemicals used by tyre manufacturers, such as mould release agents or components migrating from the rubber.

**Shelf Life :** To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

**Warranty :** © 2023, DURABLETAG

DURABLETAG' products are sold with the understanding that the Buyer will test them in actual use and determine for him/herself their adaptability to his/her intended DURABLETAG warrants to the buyer that its products are free from defects in material and workmanship, but limits its obligations under this warranty to replacement of the products shown to DURABLETAG' satisfaction to have been defective, provided that the Buyer has complied with the handling, storage and shelf life requirements as specified by DURABLETAG in applicable materials specifications.

The above warranties extend solely to Buyer and all warranty claims must be made by the Buyer. Rework or Replacement shall neither exceed nor decrease the original warranty period. The term of all warranty periods shall not exceed thirty (30) days from the date of the original shipment.

THE ABOVE WARRANTIES ARE EXCLUSIVE OF AND IN LIEU OF ALL OTHER WARRANTIES, WRITTEN OR ORAL, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE. NO IMPLIED STATUTORY WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE SHALL APPLY. DURABLETAG SHALL NOT BE LIABLE EITHER IN TORT OR IN CONTRACT FOR ANY LOSS OR DAMAGE, DIRECT, INCIDENTAL OR CONSEQUENTIAL, ARISING OUT OF THE USE OR INABILITY TO USE THE PRODUCT, OR FROM DELAY IN THE REPLACEMENT OR REPAIR OF PRODUCTS UNDER THE ABOVE WARRANTY.



# 45 ±5 g/m<sup>2</sup>

## Strong Adhesive

### APPLICATIONS

Shipping Label

Concrete Label

Strong Label

Process Tracking

Item Information

Barcode Label

Variable Label

Price Label



[www.durabletag.com](http://www.durabletag.com)