

### Strong Adhesive Labels Concrete Label

DURABLETAG

### PPL5210

TC MAT WHITE PP138 SRH -HWG2S



**Product Code: PPL5210** 

Product Name: TC MAT WHITE PP138 SRH -HWG2S

**Facestock:** Bioriented top - coated matt white polypropylene, extreme resistance to tear, puncture and tear propagation. Specially for labelling rough surfaces.

Basis Weight: 100 g/m<sup>2</sup> ISO 536

Caliper: 138 µm ISO 534

Adhesive: Aggressive adhesive, Synthetic Rubber Hotmet

Liner: Supercalendered glassine paper, havana colour, two sides

siliconize

Basis Weight: 80 g/m<sup>2</sup> ISO 536

Caliper: 68 µm ISO 534

Total Caliper: 295 µm±10% ISO 534

Initial Tack: 65 N ±10 / 25mm FTM 9 Glass

Peel Adhesion 90°: 35 N ±3 / 25mm FTM 2 St

Service Temperature: - 40 °C to 70 °C (158 °F)

Min. Application: Temp. - 5 °C

Adhesive Performance: Adhesive labels for marking and identification of irregular metal surfaces, adhesive labels for concrete surfaces, security identification labels for metal transport

**Shelf Life:** To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

Warranty: © 2023, DURABLETAG

# 88 ±5 g/m<sup>2</sup>

## **Strong Adhesive**

#### **APPLICATIONS**

Shipping Label Strong Label

Item Information

Variable Label

Concrete Label

**Process Tracking** Barcode Label

Price Label



