



High Temperature Polyester Label

DURABLETAG

PSL3060

PET TC MATT WHITE PA93-WG FSC

Product Code : PSL3060

Product Name : PET TC MATT WHITE PA93-WG FSC

Facestock : A polyester film , coated on both sides with a semi-matt, print receptive topcoat. . The smooth surface is print treated to achieve good TT printability and ink anchorage.

Basis Weight : 55 g/m² ISO 536

Caliper : 50 µm ISO 534

Adhesive : Permanent acrylic adhesive, Heat stabilized

Liner : White FSC is a supercalendered glassine paper. The liner is made from FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: FSC-C004451).

Basis Weight : 78 g/m² ISO 536

Caliper : 68 µm ISO 534

Total Caliper : 164 µm±10% ISO 534

Min. Application : Temp. 5 °C

Service Temperature : -40 °C to 220 °C

Adhesive Performance : This product is designed for the use in short term high temperature (< 220°C) environments, for example in the metal processing industry. Application tests are recommended. The high coat weight adhesive providing high tack and peel makes this product suitable for labelling rough and even slightly contaminated substrates.

Shelf Life : To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

Warranty : © 2023, DURABLETAG

DURABLETAG' products are sold with the understanding that the Buyer will test them in actual use and determine for him/herself their adaptability to his/her intended DURABLETAG warrants to the buyer that its products are free from defects in material and workmanship, but limits its obligations under this warranty to replacement of the products shown to DURABLETAG' satisfaction to have been defective, provided that the Buyer has complied with the handling, storage and shelf life requirements as specified by DURABLETAG in applicable materials specifications. The above warranties extend solely to Buyer and all warranty claims must be made by the Buyer. Rework or Replacement shall neither exceed nor decrease the original warranty period. The term of all warranty periods shall not exceed thirty (30) days from the date of the original shipment. THE ABOVE WARRANTIES ARE EXCLUSIVE OF AND IN LIEU OF ALL OTHER WARRANTIES, WRITTEN OR ORAL, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE. NO IMPLIED STATUTORY WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE SHALL APPLY. DURABLETAG SHALL NOT BE LIABLE EITHER IN TORT OR IN CONTRACT FOR ANY LOSS OR DAMAGE, DIRECT, INCIDENTAL OR CONSEQUENTIAL, ARISING OUT OF THE USE OR INABILITY TO USE THE PRODUCT, OR FROM DELAY IN THE REPLACEMENT OR REPAIR OF PRODUCTS UNDER THE ABOVE WARRANTY.



- 40 °C ~ + 220 °C

APPLICATIONS

Electronics
Appliances
Mechanical Equipment
VIN Labels
Metal Industry

Power Tools
Heavy Equipment
Boats
Variable Data
High Temperatures



www.durabletag.com