



# High Temperature Polyester Tag

DURABLETAG

# PST7050

POLYESTER 250 WHITE TAG

**Product Code :** PST7050

**Product Name :** POLYESTER 250 WHITE TAG

**Facestock :** Polyester PST7050 tag labels are designed for use in the toughest applications such as outdoors, extreme temperatures, and environments where chemical interaction is common. The smooth surface is print treated to achieve good TT printability and ink anchorage.

**Basis Weight :** 350 g/m<sup>2</sup> ±10%

**Caliper :** 250 µm ±10%

**Adhesive :** Non Adhesive Tag

**Service Temperature :** 4 °C to 300 °C / 39 °F to 572 °F

**Short Term Exposure <30 min :** 572 °F (300 °C)

**Long Term Operating Temperature :** 4 °C to 200 °C



POLYESTER 250 WHITE TAG is a hang tag label used for identification purposes in the metal industry.

- Labels for thermal transfer printers or manual annotation.
- Material resistant to adverse weather conditions.
- Labels for metals identification and traceability.
- We produce blank labels, in color or pre-printed with your logo and company information.
- Good printing quality for barcodes and QR codes. Wipe-resistant printing.

**Shelf Life :** To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

**Warranty :** © 2023, DURABLETAG

DURABLETAG' products are sold with the understanding that the Buyer will test them in actual use and determine for him/herself their adaptability to his/her intended DURABLETAG warrants to the buyer that its products are free from defects in material and workmanship, but limits its obligations under this warranty to replacement of the products shown to DURABLETAG' satisfaction to have been defective, provided that the Buyer has complied with the handling, storage and shelf life requirements as specified by DURABLETAG in applicable materials specifications. The above warranties extend solely to Buyer and all warranty claims must be made by the Buyer. Rework or Replacement shall neither exceed nor decrease the original warranty period. The term of all warranty periods shall not exceed thirty (30) days from the date of the original shipment. THE ABOVE WARRANTIES ARE EXCLUSIVE OF AND IN LIEU OF ALL OTHER WARRANTIES, WRITTEN OR ORAL, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE. NO IMPLIED STATUTORY WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE SHALL APPLY. DURABLETAG SHALL NOT BE LIABLE EITHER IN TORT OR IN CONTRACT FOR ANY LOSS OR DAMAGE, DIRECT, INCIDENTAL OR CONSEQUENTIAL, ARISING OUT OF THE USE OR INABILITY TO USE THE PRODUCT, OR FROM DELAY IN THE REPLACEMENT OR REPAIR OF PRODUCTS UNDER THE ABOVE WARRANTY.

## +4 °C ~ +300 °C

## APPLICATIONS

Pipe Labels	Wire Labels
Appliances	Heavy Equipment
Mechanical Equipment	Rebar Labels
Steel Labels	Variable Data
Metal Industry	High Temperatures

